

Jaime E. Espinosa

Phd candidate - Technical University of Madrid

[je.espinosa@alumnos.upm.es](mailto:je.espinosa@alumnos.upm.es)

**Structural bamboo culms: Prefabrication and mechanization**

# Structural bamboo culms: Prefabrication and mechanization

Jaime E. Espinosa

Phd candidate - Technical University of Madrid

[je.espinosa@alumnos.upm.es](mailto:je.espinosa@alumnos.upm.es)

## Abstract

This paper presents an analysis of the most representative projects at the studio of architecture and urban design '*bambusa espinosa*' ([www.bambusaespinosa.com](http://www.bambusaespinosa.com)) founded by the author and based in Madrid, Spain. The selected projects are taken as study cases of research by practice in the field of architectural and structural design using round-pole bamboos.

The main body of the paper is structured in three parts responding to the dimensions of the modules in the projects: bidimensional or planar modules, three-dimensional or spatial modules, and unidimensional or linear modules. System and joints are based primarily in the concept of prefabrication, implemented at different scales.

global warming is tackled simultaneously in two ways: slowing down carbon emissions related to building with steel and concrete because there is a reliable alternative, and reducing carbon concentrations in the atmosphere by sequestering it.

## Keywords

Bamboo, prefabrication, modular construction, construction systems

## **1. Introduction**

All the following projects have their design concept intimately related to the construction and structural systems implemented in every case, therefore becoming a primary part in the making of the project. Given the fact that the sites are located in countries of three continents (Africa, America and Europe), this analysis invites to reflect about the transferability of well-developed methods from one country to another.

The requirements of each client, together with the resources available and the time-span of each project, leads to a different approach from the technological point of view, which ends up in a design concept that later on shall be materialized in the building.

## **2. Methodology**

The content of the paper is structured in three chapters responding to the dimensions of the modules in the projects: bidimensional or planar modules, three-dimensional or spatial modules, and unidimensional or linear modules.

The level of complexity in the overall system and in the joints are based primarily in the concept of prefabrication, implemented at different scales and resulting in designing, for instance, iron fittings, or any other complement to bamboo, in order to make the system work efficiently.

### **2.1. Bidimensional or Planar Modules**

#### **2.1.1. Self-sustainable Boutique Lodge in Arusha (Tanzania)**

The requirements of the program shifted from a second house in the first place, to a guesthouse, and finally to a boutique lodge. The site is plot on the foothills of Mount Meru, facing Kilimanjaro and with a panoramic view of the Masai steppe.

The whole development had to be self-sufficient at every phase because of the lack of services in the area. The project is based on three strategies, dealing with energy, water and materials. Regarding the latter, bamboo and interlocking stabilized soil blocks were used instead of timber and cement blocks, which are the most common building materials in the region.

Bamboo was used for the main structure of the buildings open to public: bungalows and common area. This main structure supports the roof and consists of six triangulated, flat modules composed by beam, column and struts. These six modules are arranged radially, generating a dome with hexagonal base, joint at the peak as a reciprocal structure.

There was no bamboo for construction in the Tanzanian market at that time, so the whole industrial process related to harvest and treat it to get a high-quality building material was implemented at the building site. There were training sessions for local craftsmen to learn about building with bamboo.

### **2.1.2. Hotel Extension in Palenque (Mexico)**

The client requested the extension of the main building within a hotel compound located along the road to the Mayan site of Palenque (Chiapas, Mexico). In this case there was already treated material available in the area and experienced craftsmen in building with bamboo. A gallery running in parallel to the existing building was proposed, created by seven planar modules. Each one of them was conceived as a truss whose beam was prolonged, generating an overhang.

## **2.2. Three-dimensional or Spatial Modules**

### **2.2.1. Tensegrity Structure in Majorca (Spain)**

A tensegrity-type structure was designed and built as requested by a circus company to be perform a show on it. Its final height was 8 meters, reached by using 9 bamboo poles compressed by steel cables.

The bamboo poles were assembled previously in groups of three, each group generating two tetrahedron linked by a vertex. These groups were put together horizontally, on the ground using the steel cables. Later on, the whole, as it was already a stiff structural unity on itself, was lifted up and placed vertically on its final location.

### **2.2.2. Experimental Greenhouse in Madrid (Spain)**

The practical part of the 3-day workshop that took place at the Polytechnical University of Madrid on October 2019 aimed to execute a greenhouse at the agronomical experimental fields in the campus.

The design concept is based on structural modules which are three-dimensional and self-standing by themselves. Three of these modules were arranged together and covered with polycarbonate panels previously attached to additional bamboo planar modules on the ground.

## **2.3. Unidimensional or Lineal Modules**

### **2.3.1. Prefabricated detachable structures (various locations)**

Aiming for a design which allows to be assembled and dismantled easily, ‘bamboopod’ was conceived ([www.bamboopod.eu](http://www.bamboopod.eu)). Finally, the system to manufacture this kind of construction has been fully developed and patented. The main reasons behind the application of this design concept are to reduce the impact of logistics in the sales costs of a bamboo structures, optimize resources (thanks to the controlled working environment at the production plant), and increase precision, what reflects on the quality of the final products.

This technology focuses on placing bamboo in the mainstream as building material. The strategy to do so consists on developing products where bamboo plays a crucial role, combined selectively with other materials and adapting it to work together with construction systems available in the market.

Used as round poles, not as boards or slats, bamboo is a material which may have even positive environmental impact given its high carbon sequestration rate and the low energy consumption in processing it.

Added value driven design, prefabrication, serial production, zero waste manufacturing, ecological surplus and quality working environment are all existing concepts. However, to put them all together harmoniously related to the building industry, means an approach not seen up to date.

Primary material in the system is bamboo, but it is combined with iron fittings, PVC fabric and, and eventually aluminium based enclosure systems, such as wind blockers or curtain walls. This way, all materials used in the system are either biodegradable (bamboo), reusable (iron) or recyclable (PVC and aluminium) and therefore zero waste manufacturing achieved. Only what it is going to be built arrive at the building site, where no more than 2 persons with wrenches and ladders are required to build a given structure.

Dismantled, it is packed in a compact way; i.e., a 7x7-meter module, reaching 4 meters at the highest point, and its covering, takes only 3x1x1-meter. Thus, transport costs are reduced, both in monetary and environmental terms.

The system is conceived to be easily assembled and dismantled with requirements as low as the specified above, this makes it suitable for permanent as well as temporary use. The heaviest component in the system weights 20 kg, to be handled by 1 person. All the components are packed in boxes below 50 kg, to be carried by 2 persons. Electric tools are only used at the production plant, increasing safety.

Design principles are not a novelty (prefabrication, serial production and quality working environment among others) but to put them in practice regarding bamboo manufacturing is: Bamboo artisans shift to valued professionals through the implementation of these principles.

Combining bamboo structures with tension fabric as covering and aluminium frames-based systems as enclosures, business opportunities are also created for industry agents at final destinations, due to the competitive advantages the system may provide.

### **3. Results**

Using bamboo in its natural form as structural material shall contribute to invert the current ecological footprint of the building industry, even in countries which are non-producers. Bamboos are paramount carbon sinks, as timber, but much more renewable. When treated with environmentally friendly methods, bamboo does not stand direct rain and sun, this is the reason why all these structures are self-protected by design, all but the tensegrity in Majorca, which was meant to remain on site for only 3 months.

Protection by design is key for a long-lasting structure, as well as selection of adequate constructive systems and techniques considering the expertise of the work force involved in

the project. Despite being a material with very little similarities with the most common building materials worldwide due to the fact that it is a natural one, it is relatively easy to learn how to work with it as structural material.

Therefore, even though training is a must in almost every project, trainees are usually highly motivated and successful in learning how to work safely with structural bamboo culms.

#### **4. Conclusions**

Bamboos are fast-growing plants working as remarkable carbon sinks while alive, specially before the 5th year after sprouted: during growing and maturing stages, removes CO<sub>2</sub> at higher rates than the rest of their lives. Managing bamboo forest and plantations to take advantage of it as building material means storing carbon dioxide from the atmosphere (until that bamboo is burnt or decomposed) at the same time that it is obtained a potentially high-quality building material which might be comparable in structural performance to steel and reinforced concrete.

Therefore, global warming is tackled simultaneously in two ways: slowing down carbon emissions related to building with steel and concrete because there is a reliable alternative, and reducing carbon concentrations in the atmosphere by sequestering it.

#### **Bibliography**

Dunkelberg, K. 1985. Bamboo as Building Material. IL31 - Bamboo. Institute for Lightweight Structures (Ed.), University of Stuttgart. Stuttgart, Germany.

Engel, H. 2001. Structure Systems. Gustavo Gili Ed. Barcelona, Spain. ISBN 978-3775707060.

Escamilla, E. Z., Harbert, G. (2014) Environmental impacts of bamboo-based construction materials representing global production diversity. *Journal of Cleaner Production* 69 (2014) 117-127. Elsevier.

Forster, B.; Mollaert, M. 2009. *Arquitectura Textil: Guía Europa de Diseño de las Estructuras Tensadas*. Munillalera Ed. Madrid, Spain. ISBN 978-8489150829.

Frey, P.; von Schaewen, D. 2013. *Simon Velez: Architect Mastering Bamboo*. Actes Sud. Paris, France. ISBN 978-2330012373.

Le Corbusier 1923. *Verse une Architecture*. ISBN 0-89236-822-5.

Hidalgo-López, O. 2003. *Bamboo: The Gift of the Gods*. Oscar Hidalgo-López Ed. Bogota, Colombia. ISBN 978-9583342981.

ICONTEC (2010) NSR-10: *Reglamento Colombiano de Construcción Sismorresistente*. Capítulo G12: Estructuras de Guadua. Bogotá, Colombia.

- ISO 19624:2018 (2018), Bamboo structures—grading of bamboo culms. International Organisation of Standards.
- ISO 22156:2021 (2021), Bamboo structures—bamboo culms—structural design. International Organisation of Standards.
- ISO 22157:2019 (2019), Bamboo structures—determination of physical and mechanical properties of bamboo culms—test methods. International Organisation of Standards.
- Liese, Walter (1998) The Anatomy of Bamboo Culms. INBAR Technical report.
- McClure, F. A. (1953) Bamboo as a Building Material. Foreign Agricultural Service. United States Department of Agriculture.
- McDonough, W.; Braungart, M. 2002. Cradle to Cradle: Remaking the Way We Make Things. North Point Press. New York, the United States. ISBN 0 86547 587 3.
- Minke, G. 2012. Building with Bamboo. Birkhäuser. Basel, Switzerland. ISBN 978-3034607483.
- Pauli, G. 2010. The Blue Economy. 10 Years, 100 Innovations. 1,000 Million Jobs. Report to the Club of Rome. Paradigm Publications. Suginami, Japan. ISBN 97809122111902.
- Pradhan, N. P. N., Dimitrakopoulos, E. G. (2022) Design of multiculm bamboo members with bolted connections. International Conference on Non-conventional Materials and Technologies NOCMAT 2022.
- Stamm, J. 2001. Guía para la Construcción de Puentes en Guadua. Proyecto UTP-GTZ. JM Calle Editorial. Pereira, Colombia.
- Stulz, R.; Mukerji, K. 1993. Appropriate Building Materials. SKAT. St. Gallen, Switzerland. ISBN 3 908001 44 7.
- Van der Lugt, P. 2017. Booming Bamboo. Materia Exhibitions BV. Naarden, the Netherlands. ISBN 978-9082755206.
- Venturi, R. 1966. Complexity and Contradiction in Architecture. The Museum of Modern Art Press. New York, the United States. ISBN 0-87070-281-5.
- Vrachliotis, G.; Kleinmanns, M.; Kurz, Ph. 2016. Frei Otto: Thinking by Modeling. Spector Books. Leipzig, Germany. ISBN: 9783959050890.
- Zhaohua, Zh. and Wei, J. (2018) Sustainable Bamboo Development. CAB International.